


COORDINATED RESPONSE EXERCISE®

Pipeline Safety Training For First Responders



EMERGENCY RESPONSE MANUAL

Overview

Operator Profiles

Emergency Response

NENA Pipeline Emergency Operations

Signs of a Pipeline Release

High Consequence Area Identification

Pipeline Industry ER Initiatives

Pipeline Damage Reporting Law

2024





EMERGENCY CONTACT LIST

COMPANY	EMERGENCY NUMBER
Equitrans Midstream	1-833-929-1736

Note: The above numbers are for emergency situations.

Additional pipeline operators may exist in your area.

Visit the National Pipeline Mapping System at www.npms.phmsa.dot.gov for companies not listed above.

ONE-CALL SYSTEM	PHONE NUMBER
Virginia 811	1-800-552-7001
National One-Call Referral Number	1-888-258-0808
National One-Call Dialing Number	811

Table of Contents

Sponsor Listing	1
Overview	
Training Presentation	4
Hazardous Liquids Material Data Sheet	13
Highly Volatile Liquids Material Data Sheet	14
Natural Gas Material Data Sheet	15
Emergency Response Guidebook	
Emergency Response	17
NENA Pipeline Emergency Operations - Call Intake Checklist	19
PSAP - Notification of Potential Rupture Rule	20
Pipelines In Our Community / Pipeline Markers / Call Before You Dig	21
Signs Of A Pipeline Release / What To Do If A Leak Occurs / Pipeline Emergency	22
High Consequence Areas Identification / Identified Sites	23
Maintaining Safety and Integrity of Pipelines / How You Can Help Keep Pipelines Safe / NPMS / Training Center.	24
Pipeline Damage Reporting Law / Websites	25
About Paradigm	26



To: ALL EMERGENCY OFFICIALS From: Paradigm Liaison Services, LLC

Re: Pipeline Emergency Response Planning Information

This material is provided to your department as a reference to pipelines that operate in your state in case you are called upon to respond to a pipeline emergency.

For more information on these pipeline companies, please contact each company directly. You will find contact information for each company represented throughout the material.

This information only represents the pipeline and/or gas companies who work with our organization to provide training and communication to Emergency Response agencies such as yours. There may be additional pipeline operators in your area that are not represented in this document.

For information and mapping on other Transmission Pipeline Operators please visit the National Pipeline Mapping System (NPMS) at: https://www.npms.phmsa.dot.gov.

For information on other Gas and Utility Operators please contact your appropriate state commission office.

Further product-specific information may be found in the US Department of Transportation (DOT) *Emergency Response Guidebook for First Responders*.

The Guidebook is available at: https://www.phmsa.dot.gov/sites/phmsa.dot.gov/files/2020-08/ERG2020-WEB.pdf

Pipeline Emergency Response PLANNING INFORMATION

ON BEHALF OF:





Note: The enclosed information to assist in emergency response planning is delivered by Paradigm Liaison Services, LLC on behalf of the above sponsoring companies. Visit the National Pipeline Mapping System at https://www.npms.phmsa.dot.gov to determine additional companies operating in your area.

Pipeline Purpose and Reliability

- · Critical national infrastructure
- · Over 2.7 million miles of pipeline provide 65% of our nation's energy
- · 20 million barrels of liquid product used daily
- · 21 trillion cubic feet of natural gas used annually

Safety Initiatives

- · Pipeline location
 - Existing right-of-way (ROW)
- · ROW encroachment prevention
 - No permanent structures, trees or deeply rooted plants
- · Hazard awareness and prevention methods
- · Pipeline maintenance activities
 - Cleaning and inspection of pipeline system

Product Hazards and Characteristics

Petroleum (flow rate can be hundreds of thousands of gallons per hour)

- · Flammable range may be found anywhere within the hot zone
- · H2S can be a by-product of crude oil

Type 1 Products	Flash Point	Ignition Temperature
Gasoline	- 45 °F	600 °F
Jet Fuel	100 °F	410 °F
Kerosene	120 °F	425 °F
Diesel Fuel	155 °F	varies
Crude Oil	25 °F	varies

Natural Gas (flow rate can be hundreds of thousands of cubic feet per hour)

- · Flammable range may be found anywhere within the hot zone
- · Rises and dissipates relatively quickly
- H2S can be a by-product of natural gas PPM = PARTS PER MILLION

0.02 PPM Odor threshold10.0 PPM Eye irritation

100 PPM Headache, dizziness, coughing, vomiting

200-300 PPM
 500-700 PPM
 700-900 PPM
 Over 1000 PPM
 Respiratory inflammation within 1 hour of exposure Loss of consciousness/possible death in 30-60 min.
 Rapid loss of consciousness; death possible
 Unconsciousness in seconds; death in minutes

- · Incomplete combustion of natural gas may release carbon monoxide
- · Storage facilities may be present around populated areas/can be depleted production facilities or underground caverns

2

· Gas travel may be outside the containment vessel along the natural cavern between the pipe and soil

Highly Volatile Liquids

- Flammable range may be found anywhere within the hot zone
- · Products cool rapidly to sub-zero temperatures once outside the containment vessel
- · Vapor clouds may be white or clear

Type 3 Products	Flash Point	Ignition Temperature
Propane	- 150 °F	920-1120 °F
Butane	- 60 °F	725-850 °F

Line Pressure Hazards

- Transmission pipelines steel (high pressure: average 800-1200psi)
- Local gas pipeline transmission steel (high pressure: average 200-1000psi)
- Local gas mains and services steel and/or plastic (low to medium pressure)
 - · Mains: up to 300psi
 - · Service lines: up to regulator
 - Average 30-45psi and below
 - Can be up to 60-100psi in some areas
- · At regulator into dwelling: ounces of pressure

Leak Recognition and Response

- · Sight, sound, smell indicators vary depending on product
- · Diesel engines fluctuating RPMs
- · Black, dark brown or clear liquids/dirt blowing into air/peculiar odors/dead insects around gas line/dead vegetation
- · Rainbow sheen on the water/mud or water bubbling up/frozen area on ground/frozen area around gas meter
- · Any sign, gut feeling or hunch should be respected and taken seriously
- Take appropriate safety actions ASAP

High Consequence Area (HCA) Regulation

- · Defined by pipeline regulations 192 and 195
- · Requires specialized communication and planning between responders and pipeline/gas personnel
- May necessitate detailed information from local response agencies to identify HCAs in area

Emergency Response Basics


- · Always follow pipeline/gas company recommendations pipeline representatives may need escort to incident site
- Advance preparation
 - Get to know your pipeline operators/tour their facilities if possible
 - · Participate in their field exercises/request on-site training where available
 - Develop response plans and practice
- Planning partners
 - · Pipeline & local gas companies
 - · Police local/state/sheriff
 - Fire companies/HAZMAT/ambulance/hospitals/Red Cross
 - · LEPC/EMA/public officials
 - Environmental management/Department of Natural Resources
 - Army Corps of Engineers/other military officials
 - Other utilities
- · Risk considerations
 - Type/volume/pressure/location/geography of product
 - · Environmental factors wind, fog, temperature, humidity
 - Other utility emergencies
- Incident response
 - Always approach from upwind/park vehicle a safe distance away/if vehicle stalls DO NOT attempt to restart
 - · Gather information/establish incident command/identify command structure
 - · Initiate communications with pipeline/gas company representative ASAP
 - · Control/deny entry: vehicle, boat, train, aircraft, foot traffic, media refer all media questions to pipeline/gas reps

3

- Extinguish fires only
 - · To aid in rescue or evacuation
 - To protect exposures
 - When controllable amounts of vapor or liquid present
- Incident notification pipeline control center or local gas company number on warning marker
 - In Pipeline Emergency Response Planning Information Manual
 - · Emergency contact list in Program Guide
 - · Call immediately/provide detailed incident information
- · Pipeline security assist by noting activity on pipeline/gas facilities
 - · Report abnormal activities around facilities
 - Suspicious excavation/abandoned vehicles/non-company personnel/non-company vehicles
 - Freshly disturbed soil/perimeter abnormalities

One-Call

- · One-Call centers are not responsible for marking lines
- · Each state has different One-Call laws. Familiarize yourself with the state you are working in
- Not all states require facility owners to be members of a One-Call
- You may have to contact some facility owners on your own if they are not One-Call members
- In some states, homeowners must call before they dig just like professional excavators







Mountain Valley Mountain Valley Pipeline, LLC Joint Venture Partners In-service operations - Equitrans Midstream, operator NEXTera WGL **ENERGY** Midstream conEdison Transmission Mountain Valley **MVP Overview** 303 Miles of 42" Pipeline · Wetzel Co, WV to Pittsylvania Co, VA · Natural gas transmission line 3 Compressor Stations · Bradshaw CS (Wetzel County, WV) · Harris CS (Braxton County, WV) · Stallworth CS (Fayette County, WV) 4 Major Interconnects · Mobley Run (Wetzel County, WV) WB (Braxton County, WV) · Greene (Monroe County, WV) · Transco (Pittsylvania County, VA) LDC Taps 2 for Roanoke Gas in VA 1 for Hope Gas in WV Mountain Valley Mountain Valley Pipeline (MVP) Operations 24-hour remote monitoring and field response Remote operational control of Mainline Valves (MLV) Remote STOP capability at compressor stations and interconnects 24/7 Emergency Hotline for MVP For emergencies, or to report a problem: 1-833-929-1736

Mountain Valley

MVP Operations Managers (post in-service)

Jeff Thomas - Director Midstream Ops - NWV / OH / MVP

Wetzel Davis - Regional Manager - NWV / MVP

Rusty Bennett - Lead Supervisor - NWV / Northern MVP

TBD - Supervisor- Southern MVP

Local Field personnel


7

CORE

Local Operator Information*

- Operator and/or company name
- Pipeline systems and products
- Location of pipelines
- Pipeline size/operating pressure(s)
- Operator Response(s) to a pipeline emergency

*Information in the materials may not represent all pipeline companies in your area.



Paradium

CORE

Coordinated Response Exercise®

- Learn your roles and responsibilities as emergency responders should a pipeline emergency happen in your jurisdiction. As well as your access to resources.
- Acquaint you with the operator's ability to respond to a pipeline emergency.
- Identify the types of pipeline emergencies.
- Plan how all parties can engage in mutual assistance to minimize hazards to life, property and the environment.


Code of Federal Regulations (CFR): 49 CFR Parts 192 and 195

Roll Call: Law Enforcement, Fire, EMS, Emergency Management, Division of Forest Service, State & Federal Officials, School Officials, PSAP & Pipeline Operators



Paradijo





CORE **Integrity Management** Pipeline companies are required to have Integrity Management programs to insure safe and efficient operations: Internal and external cleaning and inspection, of the pipeline and affected areas Rights-of-Way and valves Supervisory Control and Data Acquisition (SCADA) Identification of High Consequence Areas (HCA) Aerial Rights-of-Way Patrols Public Awareness Outreach to stakeholders Participation as a member of 811. Operator Qualification (OQ) Training Local Distribution Company (LDC) · Meter Testing Leak Surveys May also be utilized on transmission pipelines

CORE

Pipeline Operators Emergency Response Plans

Natural gas and hazardous liquids

- Notify appropriate fire, police, and other public officials of gas or liquid pipeline emergencies, coordinate planned responses, and actual responses during an emergency
- Identify the type of incident
- Prompt and effective response measures
- Availability of personnel and equipment
- Make safe any actual or potential hazard to life, property, and the environment
- Incident investigation and review

Natural gas (49 CFR 192.615)

- . Establish and maintain communication with fire, police, and other public officials
- Direct actions to protect people, then property
- Emergency shutdown to minimize hazard to life, property, and the environment.
- Safely restore service

Hazardous liquid (49 CFR 195.402)

- Take necessary actions, such as emergency shutdown and pressure reduction
- · Control of released hazardous liquid or carbon dioxide at scene to minimize hazards
- Minimize public exposure to injury by taking appropriate actions such as evacuations or traffic controls
- Use instrumentation to assess vapor cloud coverage and determine hazardous areas
 Paradigm

CORE

Coordinated Response Exercise®

Discussion Based Exercise

Natural Disasters

- Tornadoes
- Wildfires/Forest Fires
- Flooding/Mudslides/Slips
- Earthquakes

Human Error

- Vehicle accidents involving above ground valve sites.
- Third party strikes by contractors and excavators
- · Agricultural activities, field tiling

National Security Threats

- Cyberterrorism involving pipeline systems
- IED's on pipeline assets

These training programs can also go hand in hand with Homeland Security Exercise and Evaluation Programs (HSEEP)





Paradion

Virtual Scenario Manager (VSM™) Map

CORE

Coordinated Response Exercise Discussion

Discussion Questions

- Pipeline Operators: How do you typically find out about an emergency, and what
 protocols go into effect when a product release occurs on your system that your local emergency responders may not be aware of (behind the scenes)?
- Emergency Responders: How will we deliver coordinated, prompt, reliable and actionable information to the whole community about what is happening? (Mission: Response; Public Information & Warning)
- Pipeline Operators: Do you always know where emergency responders will set up an Incident Command Post (ICP)?
- Emergency Responders: How will we establish and maintain a unified and coordinated operations structure that appropriately integrates all critical stakeholders and supports the execution of core capabilities? (Mission: Response; Operational Coordination)

CORE

Coordinated Response Exercise Discussion

Discussion Questions

- Pipeline Operators: How will you get access to the scene if a secured perimeter has
- Emergency Responders: How will we conduct appropriate measures to ensure the
 protection of the health and safety of the public and workers, as well as the
 environment, from all-hazards in support of responder operations and the affected
 communities? (Mission: Response; Environmental Response / Health & Safety)
- Pipeline Operators: How will you typically handle communications;
 At the scene between pipeline operators?

 - At the scene between pipeline operators and the ICP / other emergency responders
 - Between field pipeline personnel and Control Centers / SCADA Centers?
- . Emergency Responders: How can we ensure the capacity for timely communications in support of security, situational awareness, and operations by any and all means available, among and between affected communities in the impact area and all response forces? (Mission: Response; Operational Communications)

CORE

Discussion-Based Exercise Recap

- Timely notification of the incident
- Denied entry at scene of incident
- Quick access to remote valves/ICP
- Getting equipment into the area
- Communications with incident command
- Clear lines of communication (both ways)
- Face to face meetings with local officials
- Pre-planning with emergency services







National Emergency Number Association

Pipeline Emergency Operations Standard

NEMA's pipeline emergency operations workgroup recommendations

- Awareness of pipelines affecting the 911 service area
- Pipeline leak recognition and initial response actions
- Additional notices to pipeline operators

Initial intake checklist

Quick reference guide in program materials

Pipeline emergency operations standard/model recommendations

Access the full report through nena.org

"Actions taken during this time frame significantly impact the effectiveness of the response and are critical to public safety"



Paradign



New PHMSA Rule - Impact on PSAPs

For both natural gas and hazardous liquids pipelines

- Rupture mitigation valves must be installed on all newly constructed and replaced pipelines 6" in diameter or greater for onshore gas transmission, Type A gas gathering and hazardous liquid pipelines
 - This does not include natural gas distribution pipelines
- Pipeline operators must contact 9-1-1 or Emergency Management with a 'notice of potential rupture'

How does this rule potentially affect PSAPs

- How will your agency process this call when notified of a 'potential' release?
 - Will you record it and not pass it on to your response agencies?
 - Will you record and pass that information on to your response agencies?
 - Will this require your PSAP (and emergency services) to develop written policies?
 - · Where, potentially, could this call be coming from?
 - Pipeline control center locations
 - Contacting a PSAP through the non-emergency number (no Automatic
 - Number Identification (ANI), No Automatic Location Identification (ALI)
 - Is this number monitored 24/7?
- Pipeline operators were required to update their Emergency Response Plans (ERP) with this requirement in October 2022

Paradium



Product Characteristics

Hazardous Liquids

ER Guide 128 (Pages 192-193)*

- Crude oil, jet fuel, gasoline and other refined products
- Liquid in and liquid out of the pipeline

Highly Volatile Liquids

ER Guide 115 (Pages 166-167)*

- Propane, Butane, Ethane and natural gas liquids
- Liquid in and vapor out of the pipeline

Natural Gas

ER Guide 115 (Pages 166-167)*

- Gas in and gas out of the pipeline
- Odorant Mercaptan added where required

*These ER Guide and page numbers are from the 2020 edition of the Emergency Response Guidebook



Daraction



Derailments, car accidents, excavating/farming mishaps, natural disasters, and wildfires

PHMSA Advisory Bulletin (2012-08)

- Based on National Transportation Board recommendation
- Inform emergency responders about the benefits of 811
- · Identify underground utilities in the area
- Notify underground utilities in the area





Paradio

CORE **Explosive Limits Explosive Limits** Percent of Gas in Air HVL Liquefied Petroleum Gas **Natural Gas** 100% UEL 100% UEL 15% Gas in Air 10% Gas in Air Explosive Explosive 3.5% Gas in Air 100% LEL 100% LEL 2% Gas in Air Lean Lean Lower / Upper explosive limits depend on characteristics of specific product.

CORE InfraGard - Protecting Critical Infrastructure 16 Critical Infrastructure InfraGard is a partnership between the FBI Sectors: and members of the private sector for the Chemical Commercial Facilities protection of U.S. Critical Infrastructure. Communications Critical Manufacturing NFRAGARD MEMBER ALLIAN Dams Defense Industrial Base **Emergency Services** Energy Financial Services Food and Agriculture Government Facilities Healthcare and Public Health Information Technology Nuclear Reactors. Materials, and Waste Transportation Services https://infragard.org Water & Wastewater

CORE

Emergency Response Portal (ERP)

Systems


PHMSA Advisory Bulletin issued October 2010

https://my.spatialobjects.com/admin/register/ERPP

Provides agencies secure access to participating pipeline operator profiles include:

- Contact information
- Counties of operation
- Product(s) transported.

*Additional information updated to share pipeline mapping, emergency response plans.



Paradium

CORE

Pipeline Preparedness Training Center

Share with others in your agency unable to attend today's program

- Access to your local pipeline sponsor information
- Download the same documents presented in this program
- Certificate of completion provided upon completion of course



trainingcenter.pdigm.com Use Code: 2024CORE

911 Communications Director: Appreciate the opportunity to do this online and have it available for my staff. Very informative!

Battalion Chief: Thank you for the information: I also like the fact of being able to take the course online when I cannot make the live sessions.

Commissioner: Very Informative and increased my awareness of the resources available to our county leadership in case of an emergency.

Deputy Emergency Management Coordinator: Excellent presentation, Thank you for the resources and useful web pages.

Director of Public Safety: Excellent presentation. Thank you for the ability to take class online due to scheduling conflict.

Fire Chief: Thank you for providing this informative course. I would like to see more courses like this, It is a very good review and helps us tremendously.

Police Chief: The training is very informative, and I will pass this onto our Fire Department and our Law Enforcement Supervisors. Great job | | |

Paradio

Hazardous Liquids Material Data Sheet

- POTENTIAL HAZARDS -

FIRE OR EXPLOSION

- HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.
- Vapors may form explosive mixtures with air.
- Vapors may travel to source of ignition and flash back.
- Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Vapor explosion hazard indoors, outdoors or in sewers.
- Those substances designated with a "P" may polymerize explosively when heated or involved in a fire.
- Runoff to sewer may create fire or explosion hazard.
- · Containers may explode when heated.
- · Many liquids are lighter than water.
- · Substance may be transported hot.
- If molten aluminum is involved, refer to GUIDE 169.

HFAITH

- Inhalation or contact with material may irritate or burn skin and eyes.
- Fire may produce irritating, corrosive and/ or toxic gases.
- · Vapors may cause dizziness or suffocation.
- Runoff from fire control or dilution water may cause pollution.

PUBLIC SAFETY

- CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available appropriate telephone numbers can be found in the Emergency Response Guidebook.
- As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions.
- · Keep unauthorized personnel away.
- · Stay upwind.
- Keep out of low areas.
- Ventilate closed spaces before entering.

PROTECTIVE CLOTHING

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Structural firefighters' protective clothing will only provide limited protection.

EVACUATION

Large Spill

• Consider initial downwind evacuation for at least 300 meters (1000 feet).

Fire

 If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

FIRE

CAUTION: All these products have a very low flash point: Use of water spray when fighting fire may be inefficient.
CAUTION: For mixtures containing alcohol or polar solvent, alcohol-resistant foam may be more effective.

Small Fire

Dry chemical, CO2, water spray or regular foam.

Large Fire

listed.

· Water spray, fog or regular foam.

PRODUCT: Crude Oil **DOT GUIDEBOOK ID #:** GUIDE #: 128 **PRODUCT:** Diesel Fuel **DOT GUIDEBOOK ID #:** GUIDE #: 128 **PRODUCT:** Jet Fuel **DOT GUIDEBOOK ID #:** GUIDE #: 1863 128 **PRODUCT:** Gasoline **DOT GUIDEBOOK ID #:** GUIDE #: 128 Refer to the Emergency Response Guidebook for additional products not

 Use water spray or fog; do not use straight streams

EMERGENCY RESPONSE

 Move containers from fire area if you can do it without risk.

Fire involving Tanks or Car/Trailer Loads

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

SPILL OR LEAK

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.
- Prevent entry into waterways, sewers, basements or confined areas.
- A vapor suppressing foam may be used to reduce vapors.
- Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
- Use clean non-sparking tools to collect absorbed material.

FIRST AID

- · Move victim to fresh air.
- Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- · Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- · Wash skin with soap and water.
- In case of burns, immediately cool affected skin for as long as possible with cold water.
 Do not remove clothing if adhering to skin.
- · Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

Highly Volatile Liquids Material Data Sheet

- POTENTIAL HAZARDS –

FIRE OR EXPLOSION

- EXTREMELY FLAMMABLE...
- · Will be easily ignited by heat, sparks or
- Will form explosive mixtures with air.
- · Vapors from liquefied gas are initially heavier than air and spread along ground. CAUTION: Hydrogen (UN1049), Deuterium (UN1957), Hydrogen, refrigerated liquid (UN1966) and Methane (UN1971) are lighter than air and will rise. Hydrogen and Deuterium fires are difficult to detect since they burn with an invisible flame. Use an alternate method of detection (thermal camera, broom handle, etc.)
- Vapors may travel to source of ignition and flash back.
- Cylinders exposed to fire may vent and release flammable gas through pressure relief devices.
- Containers may explode when heated.
- · Ruptured cylinders may rocket.

HEALTH

- Vapors may cause dizziness or asphyxiation without warning.
- Some may be irritating if inhaled at high concentrations.
- Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite.
- Fire may produce irritating and/or toxic

PUBLIC SAFETY

- CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available appropriate telephone numbers can be found in the **Emergency Response Guidebook.**
- As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Many gases are heavier than air and will spread along ground and collect in low

EMERGENCY RESPONSE-

- or confined areas (sewers, basements, tanks).
- Keep out of low areas.

PROTECTIVE CLOTHING

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Structural firefighters' protective clothing will only provide limited protection.
- Always wear thermal protective clothing when handling refrigerated/cryogenic liquids.

EVACUATION

Large Spill

Consider initial downwind evacuation for at least 800 meters (1/2 mile).

Fire

· If tank, rail car or tank truck is involved in a fire, ISOLATE for 1600 meters (1 mile) in all directions; also, consider initial evacuation for 1600 meters (1 mile) in all directions.

FIRE

 DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED. CAUTION: Hydrogen (UN1049), Deuterium (UN1957) and Hydrogen, refrigerated liquid (UN1966) burn with an invisible flame. Hydrogen and Methane mixture, compressed (UN2034) may burn with an invisible flame.

Small Fire

· Dry chemical or CO2.

PRODUCT: Propane

DOT GUIDEBOOK ID #:

115

GUIDE #:

GUIDE #:

PRODUCT: Butane

DOT GUIDEBOOK ID #:

115

PRODUCT: Ethane

DOT GUIDEBOOK ID #:

GUIDE #: 115

PRODUCT: Propylene

DOT GUIDEBOOK ID #:

1075/1077

GUIDE #: 115

PRODUCT: Natural Gas Liquids DOT GUIDEBOOK ID #:

GUIDE #: 115

Refer to the Emergency Response Guidebook for additional products not listed.

Large Fire

- · Water spray or fog.
- Move containers from fire area if you can do it without risk.

Fire involving Tanks

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles
- Cool containers with flooding quantities of water until well after fire is out.
- Do not direct water at source of leak or safety devices; icing may occur.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire

SPILL OR LEAK

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Do not touch or walk through spilled
- Stop leak if you can do it without risk.
- If possible, turn leaking containers so that gas escapes rather than liquid.
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
- Do not direct water at spill or source of

- · Prevent spreading of vapors through sewers, ventilation systems and confined areas
- Isolate area until gas has dispersed. **CAUTION: When in contact with** refrigerated/cryogenic liquids, many materials become brittle and are likely to break without warning.

FIRST AID

- Move victim to fresh air.
- Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes
- Clothing frozen to the skin should be thawed before being removed.
- In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
- In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin.
- · Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

POTENTIAL HAZARDS -

FIRE OR EXPLOSION

- EXTREMELY FLAMMABLE.
- · Will be easily ignited by heat, sparks or
- Will form explosive mixtures with air.
- Vapors from liquefied gas are initially heavier than air and spread along ground. CAUTION: Hydrogen (UN1049), Deuterium (UN1957), Hydrogen, refrigerated liquid (UN1966) and Methane (UN1971) are lighter than air and will rise. Hydrogen and Deuterium fires are difficult to detect since they burn with an invisible flame. Use an alternate method of detection (thermal camera, broom handle, etc.)
- Vapors may travel to source of ignition and flash back.
- Cylinders exposed to fire may vent and release flammable gas through pressure relief devices.
- Containers may explode when heated.
- · Ruptured cylinders may rocket.

HFAITH

- Vapors may cause dizziness or asphyxiation without warning.
- Some may be irritating if inhaled at high concentrations.
- Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite.
- Fire may produce irritating and/or toxic

PUBLIC SAFETY

- CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available appropriate telephone numbers can be found in the **Emergency Response Guidebook.**
- As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.
- Many gases are heavier than air and will spread along ground and collect in low

EMERGENCY RESPONSE-

- or confined areas (sewers, basements, tanks).
- Keep out of low areas.

PROTECTIVE CLOTHING

- · Wear positive pressure self-contained breathing apparatus (SCBA).
- Structural firefighters' protective clothing will only provide limited protection.
- Always wear thermal protective clothing when handling refrigerated/cryogenic liquids.

EVACUATION

Large Spill

· Consider initial downwind evacuation for at least 800 meters (1/2 mile).

· If tank, rail car or tank truck is involved in a fire, ISOLATE for 1600 meters (1 mile) in all directions; also, consider initial evacuation for 1600 meters (1 mile) in all directions.

• DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED. CAUTION: Hydrogen (UN1049), Deuterium (UN1957) and Hydrogen, refrigerated liquid (UN1966) burn with an invisible flame. Hydrogen and Methane with an invisible flame.

· Dry chemical or CO2.

Large Fire

- · Water spray or fog.
- Move containers from fire area if you can do it without risk.

Fire involving Tanks

- · Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- · Cool containers with flooding quantities of water until well after fire is out.
- · Do not direct water at source of leak or safety devices; icing may occur.
- · Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- · ALWAYS stay away from tanks engulfed in
- · For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

SPILL OR LEAK

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Do not touch or walk through spilled material
- Stop leak if you can do it without risk.
- If possible, turn leaking containers so that gas escapes rather than liquid.
- Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.
- Do not direct water at spill or source of
- Prevent spreading of vapors through sewers, ventilation systems and confined

Isolate area until gas has dispersed. **CAUTION: When in contact with** refrigerated/cryogenic liquids, many materials become brittle and are likely to break without warning.

FIRST AID

- · Move victim to fresh air.
- Call 911 or emergency medical service.
- Give artificial respiration if victim is not
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- Clothing frozen to the skin should be thawed before being removed.
- In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
- In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin.
- Keep victim warm and quiet.
- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

mixture, compressed (UN2034) may burn

Small Fire

DOT GUIDEBOOK ID #: GUIDE #: 1971 115

CHEMICAL NAMES:

- Natural Gas
- Methane
- Marsh Gas
- · Well Head Gas
- Fuel Gas
- · Lease Gas
- Sour Gas*


CHEMICAL FAMILY:

Petroleum Hydrocarbon Mix: Aliphatic Hydrocarbons (Alkanes), Aromatic Hydrocarbons, Inorganic Compounds

COMPONENTS:

Methane, Iso-Hexane, Ethane, Heptanes, Propane, Hydrogen Sulfide*, (In "Sour" Gas), Iso-Butane, Carbon, Dioxide, n-Butane, Nitrogen, Pentane Benzene, Hexane, Octanes

Product INFORMATION



The Emergency Response Guidebook is available at: https://www.phmsa.dot.gov/sites/phmsa.dot.gov/site







This app is only available on the App Store for iOS devices.

Emergency Response

Emergency Response Plans for Gas and Hazardous Liquid Pipeline Operators

Federal regulations for both gas and hazardous liquid pipelines require operators to have written procedures for responding to emergencies involving their pipeline facility. Because pipelines are often located in public space, the regulations further require that operators include procedures for planning with emergency and other public officials to ensure a coordinated response. Please contact your local pipeline operators for information regarding their company specific emergency response plan.

Natural Gas

Each operator shall establish written procedures to minimize the hazard resulting from a gas pipeline emergency. At a minimum, the procedures must provide for the following:

- · Receiving, identifying, and classifying notices of events which require immediate response by the operator.
- Establishing and maintaining adequate means of communication with appropriate fire, police, and other public officials.
- Prompt and effective response to a notice of each type of emergency, including the following:
 - 1. Gas detected inside or near a building.
 - 2. Fire located near or directly involving a pipeline facility.
 - Explosion occurring near or directly involving a pipeline facility.
 - 4. Natural disaster.
- · The availability of personnel, equipment, tools, and materials, as needed at the scene of an emergency.
- Actions directed toward protecting people first and then property.
- Emergency shutdown and pressure reduction in any section of the operator's pipeline system necessary to minimize hazards to life or property.
- Making safe any actual or potential hazard to life or property.
- Notifying appropriate fire, police, and other public officials of gas pipeline emergencies and coordinating with them both planned responses and actual responses during an emergency.
- Safely restoring any service outage.
- · Each operator shall establish and maintain liaison with appropriate fire, police, and other public officials to:
 - 1. Learn the responsibility and resources of each government organization that may respond to a gas pipeline emergency;
 - 2. Acquaint the officials with the operator's ability in responding to a gas pipeline emergency;
 - 3. Identify the types of gas pipeline emergencies of which the operator notifies the officials; and
 - 4. Plan how the operator and officials can engage in mutual assistance to minimize hazards to life or property.

*Reference 49 CFR 192.615

Hazardous Liquids


(a) **General:** Each operator shall prepare and follow for each pipeline system a manual of written procedures for conducting normal operations and maintenance activities and handling abnormal operations and emergencies. This manual shall be reviewed at intervals not exceeding 15 months, but at least once each calendar year, and appropriate changes made as necessary to insure that the manual is effective. This manual shall be prepared before initial operations of a pipeline system commence, and appropriate parts shall be kept at locations where operations and maintenance activities are conducted.


Emergencies. The manual required by paragraph (a) of this section must include procedures for the following to provide safety when an emergency condition occurs:

- Receiving, identifying, and classifying notices of events which need immediate response by the operator or notice to fire, police, or other appropriate public officials and communicating this information to appropriate operator personnel for corrective action.
- Prompt and effective response to a notice of each type emergency, including fire or explosion occurring near or directly involving a pipeline facility, accidental release of hazardous liquid or carbon dioxide from a pipeline facility, operational failure causing a hazardous condition, and natural disaster affecting pipeline facilities.
- Having personnel, equipment, instruments, tools, and material available as needed at the scene of an emergency.
- Taking necessary action, such as emergency shutdown or pressure reduction, to minimize the volume of hazardous liquid
 or carbon dioxide that is released from any section of a pipeline system in the event of a failure.
- Control of released hazardous liquid or carbon dioxide at an accident scene to minimize the hazards, including possible intentional ignition in the cases of flammable highly volatile liquid.
- Minimization of public exposure to injury and probability of accidental ignition by assisting with evacuation of residents and assisting with halting traffic on roads and railroads in the affected area, or taking other appropriate action.
- Notifying fire, police, and other appropriate public officials of hazardous liquid or carbon dioxide pipeline emergencies and coordinating with them preplanned and actual responses during an emergency, including additional precautions necessary for an emergency involving a pipeline system transporting a highly volatile liquid.
- In the case of failure of a pipeline system transporting a highly volatile liquid, use of appropriate instruments to assess the extent and coverage of the vapor cloud and determine the hazardous areas.
- Providing for a post accident review of employee activities to determine whether the procedures were effective in each emergency and taking corrective action where deficiencies are found.

*Reference 49 CFR 195.402

Emergency Response





NENA Pipeline Emergency Operations - Call Intake Checklist

In accordance with NENA Pipeline Emergency Operations Standard/Model Recommendation NENA 56-007 (https://www.nena.org/?page=PipelineEmergStnd)

GOALS FOR INITIAL INTAKE:

- 1. Obtain and Verify Incident Location, Callback and Contact Information
- 2. Maintain Control of the Call
- 3. Communicate the Ability to HELP the Caller
- Methodically and Strategically Obtain Information through Systematic Inquiry to be Captured in the Agency's Intake Format
- 5. Recognize the potential urgency of situations involving the release of dangerous gases or liquids related to pipelines or similar events of this nature and immediately begin the proper notifications consistent with agency policy
- 6. Perform all Information Entries and Disseminations, Both Initial and Update

FIRST RESPONSE CALL INTAKE CHECKLIST

The focus of this Standard is on the first minute of the call intake process. Actions taken during this time frame significantly impact the effectiveness of the response and are critical to public safety.

The following protocol is intended as a solid framework for call intake, but should not in any manner rescind or override agency procedures for the timing of broadcasts and messaging.

These procedures are established as recommended practices to consider with existing agency policy and procedure to ensure the most swift and accurate handling of every incident involving the release of dangerous gases or hazardous liquids.

All information should be simultaneously entered, as it is obtained by the telecommunicator, into an electronic format (when available) that will feed/populate any directed messages which will be sent to emergency responders in conjunction with onair broadcasts.

Location:

Request exact location of the incident (structure addresses, street names, intersections, directional identifiers, mile posts, etc.) and obtain callback and contact information.

Determine Exactly What Has Happened:

Common signs of a pipeline leak are contained in Table 1 below. If any of these conditions are reported, THIS IS A PIPELINE EMERGENCY.

TABLE 1
Common Indications of a Pipeline Leak

Condition	Natural Gas (lighter than air)	LPG & HVL (heavier than air)	Liquids
An odor like rotten eggs or a burnt match	Х	Х	
A loud roaring sound like a jet engine	Х	Х	
A white vapor cloud that may look like smoke		X	
A hissing or whistling noise	Х	Х	
The pooling of liquid on the ground			Х
An odor like petroleum liquids or gasoline		Х	Х
Fire coming out of or on top of the ground	Х	Х	
Dirt blowing from a hole in the ground	Х	Х	
Bubbling in pools of water on the ground	Х	Х	
A sheen on the surface of water		Х	Х
An area of frozen ground in the summer	Х	Х	
An unusual area of melted snow in the winter	Х	Х	
An area of dead vegetation	Х	Х	Х

PSAP - Notification of Potential Rupture Rule

From April Heinze at NENA October 2022

A recent change made at the federal level will begin to impact your Emergency Communications Center (ECC) very soon. In April 2022, the Pipeline and Hazardous Materials Safety Administration (PHMSA), a subset of the National Highway Traffic Safety Administration (NHTSA), updated a rule for Pipeline Operators. The rule went into effect on October 5, 2022. The PHMSA rule is 49 CFR § 192.615(a)(8) and § 195.402(e)(7). It requires pipeline operators to contact the appropriate PSAP immediately upon notification of a potential rupture. The rule specifies the following:

A **Notification of Potential Rupture** is an observation of any unanticipated or unexplained:

- Pressure loss outside of the pipeline's normal operating pressure
- Rapid release of a large volume of a commodity (e.g., natural gas or hazardous liquid)
- · Fire or explosion in the immediate vicinity

ECCs will begin to receive calls from pipeline operators for situations that may not be dispatchable. Of the three potential rupture notifications, the "pressure loss outside of the pipeline's normal operating pressure" will be the most difficult for responders to locate and mitigate. The operators will contact the ECC at the same time they are sending a technician to check the potential problem and determine the actual location. Many pipeline segments span an extensive area that could cross multiple ECC and Fire Department boundaries. Based on recent discussions with pipeline operators, they will call ECCs to fulfill the rule requirements to place the ECC on standby for a potential problem. They also want the ECC to contact them if the ECC receives any calls that may confirm there is a problem.

PHMSA and pipeline operators lack an understanding of local ECC and first responder policies and procedures. Some pipeline operators have already sent letters to ECCs that serve the areas their pipeline infrastructure is located. It does not appear that PHMSA engaged the ECC community before adopting the rule, nor have they communicated this information to the responder community.

So, what does this mean for your ECC? ECCs are responsible for intaking information and dispatching appropriate resources. They are not in the habit of intaking details of a potential emergency and doing nothing with it. To do nothing creates liability issues for your ECC. ECC Managers should work with local Fire Departments to develop local policy regarding handling these calls. The policy will need to address whether to hold the information until further information is provided from the pipeline operator or, if a dispatch is to be made, what resources need to be sent. The policy should also address how to properly notify the pipeline operator if the ECC or responders discover that a potential rupture is, in fact, an actual rupture. ECC management should incorporate pipeline maps into their local GIS systems or maintain a map easily accessible to call-takers of the pipeline infrastructure within their jurisdiction. PHMSA has a pipeline mapping system that ECCs can use, https://www.npms.phmsa.dot.gov/. In addition, the ECC should consider specific questions within their call intake guides.

Specific Questions that ECCs may want to incorporate for potential rupture situations include:

- 1. What commodity might be leaking, and how severe does the potential leak appear?
- 2. What is the point-to-point location span of the potential rupture?
- 3. Is any special equipment needed for responders to mitigate the potential problem?

To comply with the new PHMSA rule, pipeline operators must contact ECCs reliably. Some pipeline operators are local or regional companies with existing relationships with the ECCs in their area. However, many pipeline operators serve a large geographic area and may not have established relationships with every ECC within their service area. Those pipeline operators may utilize the NENA Enhanced PSAP Registry and Census (EPRC) to obtain PSAP contact information. NENA strongly encourages you to verify the accuracy of your PSAP's contact information in the EPRC database. ECC 24/T/365 emergency contact number(s) should be 10-digit lines answered as quickly as possible. Callers should not be required to interact with a phone tree or wait on hold if possible. Access to the EPRC is free for ECCs. To learn more and to request user accounts if you do not already use the EPRC, visit nena.org/eprc.

Pipelines In Our Community

According to National Transportation Safety Board statistics pipelines are the safest and most efficient means of transporting natural gas and petroleum products, which are used to supply roughly two-thirds of the energy we use. These pipelines transport trillions of cubic feet of natural gas and hundreds of billions of ton/miles of liquid petroleum products in the United States each year.

This system is comprised of three types of pipelines: transmission, distribution and gathering. The approximately 519,000 miles of transmission pipeline* transport products, including natural gas and petroleum products, across the country and to storage facilities. Compressor stations and pumping stations are located along transmission and gathering pipeline routes and help push these products through the line.

Approximately 2.2 million miles of distribution pipeline* is used to deliver natural gas to most homes and businesses through underground main and utility service lines. Onshore gathering lines are pipelines that transport gas from a current production operation facility to a transmission line or main. Production operations are piping and equipment used in production and preparation for transportation or delivery of hydrocarbon gas and/or liquids.

*mileage according to the Pipeline Hazardous Materials Safety Administration (PHMSA).

Pipeline Markers

The U.S. Department of Transportation (DOT) requires the use of signs to indicate the location of underground pipelines. Markers like these are located on road, railroad, and navigable waterway crossings. Markers are also posted along the pipeline right-of-way.

The markers display:

- · The material transported
- The name of the pipeline operator
- The operator's emergency number

MARKER INFORMATION


- · Indicates area of pipeline operations
- May have multiple markers in single right-of-way
- · May have multiple pipelines in single right-of-way
- · DOES NOT show exact location
- DOES NOT indicate depth (never assume pipeline depth)
- DOES NOT indicate pipeline pressure



Call Before You Dig

Statistics indicate that damage from excavation related activities is a leading cause of pipeline accidents. If you are a homeowner, farmer, excavator, or developer, we need your help in preventing pipeline emergencies.

- 1. Call your state's One-Call center before excavation begins regulatory mandate as state law requires.
- 2. Wait the required amount of time.
- 3. A trained technician will mark the location of the pipeline and other utilities (private lines are not marked).
- Respect the marks.
- 5. Dig with care.



National One-Call Dialing Number:



For More Details Visit: www.call811.com

Signs Of A Pipeline Release

SIGHT*

- · Liquid on the ground
- · Rainbow sheen on water
- Dead vegetation in an otherwise green area
- · Dirt blowing into the air
- · White vapor cloud
- · Mud or water bubbling up
- · Frozen area on ground
- *Signs vary based upon product

SMELL

- · Odors such as gas or oil
- · Natural gas is colorless and odorless
 - Unless Mercaptan has been added (rotten egg odor)

OTHER-NEAR PIPELINE OPERATIONS

- Burning eyes, nose or throat
- Nausea

What To Do If A Leak Occurs

- · Evacuate immediately upwind
- · Eliminate ignition sources
- · Advise others to stay away
- CALL 911 and the pipeline company number on warning marker
 - Call collect if necessary
- · Make calls from safe distance not "hot zone"
- · Give details to pipeline operator:
 - Your name
 - Your phone number
 - Leak location
 - Product activity
 - Extent of damage
- · DO NOT drive into leak or vapor cloud
- · DO NOT make contact with liquid or vapor
- DO NOT operate pipeline valves (unless directed by pipeline operator):
 - Valve may be automatically shut by control center
 - Valve may have integrated shut-down device

 Valve may be operated by qualified pipeline personnel only, unless specified otherwise

SOUND

A hissing or roaring sound

- Ignition sources may vary a partial list includes:
 - Static electricity
 - Metal-to-metal contact
 - Pilot lights
 - Matches/smoking
 - Sparks from telephone
 - Electric switches
 - Electric motors
 - Overhead wires
 - Internal combustion engines
 - · Garage door openers
 - Firearms
 - · Photo equipment
 - Remote car alarms/door locks
 - High torque starters diesel engines
 - · Communication devices

Pipeline Emergency

Call Gas Control Or Pipeline Control Center

Use *Pipeline Emergency Response Planning Information Manual* for contact information Phone number on warning markers
Use state One-Call System, if applicable

Control Center Needs To Know

Your name & title in your organization
Call back phone number – primary, alternate
Establish a meeting place
Be very specific on the location *(use GPS)*Provide City, County and State

Injuries, Deaths, Or Property Damage

Have any known injuries occurred?
Have any known deaths occurred?
Has any severe property damage occurred?

Traffic & Crowd Control

Secure leak site for reasonable distance Work with company to determine safety zone No traffic allowed through any hot zone Move sightseers and media away Eliminate ignition sources

Fire

Is the leak area on fire?
Has anything else caught on fire besides the leak?

Evacuations

Primary responsibility of emergency agency Consult with pipeline/gas company

Fire Management

Natural Gas – DO NOT put out until supply stopped Liquid Petroleum – water is NOT recommended; foam IS recommended
Use dry chemical, vaporizing liquids, carbon dioxide

Ignition Sources

Static electricity (nylon windbreaker) Metal-to-metal contact

Pilot lights, matches & smoking, sparks from phone Electric switches & motors

Overhead wires

Internal combustion engines

Garage door openers, car alarms & door locks

Firearms

Photo equipment

High torque starters – diesel engines

Communication devices - not intrinsically safe

High Consequence Areas Identification*

Pipeline safety regulations use the concept of "High Consequence Areas" (HCAs), to identify specific locales and areas where a release could have the most significant adverse consequences. Once identified, operators are required to devote additional focus, efforts, and analysis in HCAs to ensure the integrity of pipelines.

Releases from pipelines can adversely affect human health and safety, cause environmental degradation, and damage personal or commercial property. Consequences of inadvertent releases from pipelines can vary greatly, depending on where the release occurs, and the commodity involved in the release.

What criteria define HCAs for pipelines?

Because potential consequences of natural gas and hazardous liquid pipeline releases differ, criteria for HCAs also differ. HCAs for natural gas transmission pipelines focus solely on populated areas. (Environmental and ecological consequences are usually minimal for releases involving natural gas.) Identification of HCAs for hazardous liquid pipelines focuses on populated areas, drinking water sources, and unusually sensitive ecological resources.

HCAs for hazardous liquid pipelines:

- Populated areas include both high population areas (called "urbanized areas" by the U.S. Census Bureau) and other populated areas (areas referred to by the Census Bureau as a "designated place").
- Drinking water sources include those supplied by surface water or wells and where a secondary source of water

- supply is not available. The land area in which spilled hazardous liquid could affect the water supply is also treated as an HCA.
- Unusually sensitive ecological areas include locations where critically imperiled species can be found, areas where multiple examples of federally listed threatened and endangered species are found, and areas where migratory water birds concentrate.

HCAs for natural gas transmission pipelines:

- An equation has been developed based on research and experience that estimates the distance from a potential explosion at which death, injury or significant property damage could occur. This distance is known as the "potential impact radius" (or PIR), and is used to depict potential impact circles.
- Operators must calculate the potential impact radius for all points along their pipelines and evaluate corresponding impact circles to identify what population is contained within each circle.
- Potential impact circles that contain 20 or more structures intended for human occupancy; buildings housing populations of limited mobility; buildings that would be hard to evacuate. (Examples are nursing homes, schools); or buildings and outside areas occupied by more than 20 persons on a specified minimum number of days each year, are defined as HCA's.

Identified Sites*

Owners and companies of gas transmission pipelines are regulated by the US Department of Transportation (DOT). According to integrity management regulations, gas pipeline companies are required to accept the assistance of local public safety officials in identifying certain types of sites or facilities adjacent to the pipeline which meets the following criteria:

- (a) A small, well-defined outside area that is occupied by twenty or more persons on at least 50 days in any twelve-month period (the days need not be consecutive). Examples of such an area are playgrounds, parks, swimming pools, sports fields, and campgrounds.
- (b) A building that is occupied by 20 or more persons on at least 5 days a week for 10 weeks in any 12 month period (the days and weeks need not be consecutive). Examples included in the definition are: religious facilities, office buildings, community centers, general stores, 4-H facilities, and roller rinks.
- (c) A facility that is occupied by persons who are confined, are of impaired mobility, or would be difficult to evacuate. Examples of such a facility are hospitals, schools, elder care, assisted living/nursing facilities, prisons and child daycares.

Sites within your jurisdiction will fit the above requirements, please go to my.spatialobjects.com/admin/register/ISR to provide this valuable information to pipeline companies.

* 49 CFR §192.903.

IDENTIFIED SITE REGISTRY

Pipeline operators need your help keeping people and property safe.

Identified Sites - locations where many people occupy an area near a pipeline asset or facility. These are places where people may gather from time to time for a variety of reasons.

Some of these sites are very difficult for companies to obtain without help from those with local knowledge of the area.

Please use the following website to gain secure access, so you can assist in identifying sites where people congregate in your community:

my.spatialobjects.com/admin/register/ISR

Pipeline operators are required by law to work with public officials who have safety or emergency response, or planning responsibilities that can provide quality information regarding identified sites.



^{*} https://primis.phmsa.dot.gov/comm/FactSheets/FSHCA.htm

Maintaining Safety and Integrity of Pipelines

Pipeline companies invest significant time and capital maintaining the quality and integrity of their pipeline systems. Most active pipelines are monitored 24 hours a day via manned control centers. Pipeline companies also utilize aerial surveillance and/or on-ground observers to identify potential dangers. Control center personnel continually monitor the pipeline system and assess changes in pressure and flow. They notify field personnel if there is a possibility of a leak. Automatic shut-off valves are sometimes utilized

to isolate a leak. Gas transmission and hazardous liquid pipeline companies have developed supplemental hazard and assessment programs known as Integrity Management Programs (IMPs). IMPs have been implemented for areas designated as "high consequence areas" (HCAs) in accordance with federal regulations. Specific information about companies' programs may be found on their company web sites or by contacting them directly.

How You Can Help Keep Pipelines Safe

While accidents pertaining to pipeline facilities are rare, awareness of the location of the pipeline, the potential hazards, and what to do if a leak occurs can help minimize the number of accidents. A leading cause of pipeline incidents is third-party excavation damage. Pipeline companies are responsible for the safety and security of their respective pipelines. To help maintain the integrity of pipelines and their right-of-way, it is essential that pipeline and facility neighbors protect against unauthorized excavations or other destructive activities. You can help by:

- Being aware of any unusual or suspicious activities or unauthorized excavations taking place within or near the pipeline right-of-way or pipeline facility.
 - Develop contacts and relationships with pipeline company representatives, i.e. participate in mock drill exercises with your local pipeline company.
 - Share intelligence regarding targeting of national infrastructure, and specific threats or actual attacks against pipeline companies.

- Assist with security steps for pipeline facilities during heightened national threat levels, i.e., increased surveillance near facilities.
- Monitor criminal activity at the local level that could impact pipeline companies, and anti-government/ pipeline groups and other groups seeking to disrupt pipeline company activities.
- Keeping the enclosed fact sheets for future reference.
- Attending an emergency response training program in your area.
- Familiarizing yourself and your agency with the Pipelines and Informed Planning Alliance (PIPA) best practices regarding land use planning near transmission pipelines.
- Completing and returning the enclosed postage-paid survey.
- Report to the pipeline company localized flooding, ice dams, debris dams, and extensive bank erosion that may affect the integrity of pipeline crossings.

National Pipeline Mapping System (NPMS)

The National Pipeline Mapping System (NPMS) is a geographic information system created by the U.S. Department of Transportation (DOT), Pipeline and Hazardous Materials Safety Administration (PHMSA), Office of Pipeline Safety (OPS) in cooperation with other federal and state governmental agencies and the pipeline industry to provide information about companies and their pipelines. The NPMS web site is searchable by ZIP Code or by county and state, and can display a printable county map.

Within the NPMS, PHMSA has developed the Pipeline Integrity Management Mapping Application (PIMMA) for use by pipeline companies and federal, state, and

local government officials only. The application contains sensitive pipeline infrastructure information that can be viewed via internet browsers. Access to PIMMA is limited to federal, pipeline companies. PIMMA access cannot be given to any person who is not a direct employee of a government agency.

For a list of companies with pipelines in your area and their contact information, or to apply for PIMMA access, go to npms.phmsa.dot.gov. Companies that operate production facilities, gas/liquid gathering piping, and distribution piping are not represented by NPMS nor are they required to be.

Training Center

Supplemental training available for agencies and personnel that are unable to attend:

- · Train as your schedule allows
- Download resources including pipeline operator specific information
 - Sponsoring pipeline operator contact information
 - Product(s) transported

- Submit Agency Capabilities Survey
- · Receive Certificate of Completion

Visit https://trainingcenter.pdigm.com/ to register for training



Pipeline Damage Reporting Law / Websites

PIPELINE DAMAGE REPORTING LAW AS OF 2007

H.R. 2958 Emergency Alert Requirements

Any person, including a government employee or contractor, who while engaged in the demolition, excavation, tunneling, or construction in the vicinity of a pipeline facility;

- **A.** Becomes aware of damage to the pipeline facility that may endanger life or cause serious bodily harm or damage to property; or
- **B.** Damages the pipeline facility in a manner that may endanger life or cause serious bodily harm or damage to property, shall promptly report the damage to the operator of the facility and to other appropriate authorities.

Websites:

Association of Public-Safety Communications Officials - International (APCO) www.apcointl.org/

Common Ground Alliance www.commongroundalliance.com

Federal Emergency Management Agency www.fema.gov

Federal Office of Pipeline Safety www.phmsa.dot.gov

Government Emergency Telecommunications www.dhs.gov/government-emergency-telecommunications-service-gets

Infrastructure Protection – NIPC www.dhs.gov/national-infrastructure-protection-plan

National Emergency Number Association www.nena.org/?

National Fire Protection Association (NFPA) www.nfpa.org

National Pipeline Mapping System https://www.npms.phmsa.dot.gov

National Response Center https://www.epa.gov/emergency-response/national-response-center

Paradigm Liaison Services, LLC www.pdigm.com

United States Environmental Protection Agency (EPA)
www.epa.gov/cameo

Wireless Information System for Emergency Responders (WISER) https://wiser.nlm.nih.gov/

FOR MORE INFORMATION ON THE NASFM PIPELINE EMERGENCIES PROGRAM www.pipelineemergencies.com

FOR EMERGENCY RESPONSE INFORMATION, REFER TO DOT GUIDEBOOK. FOR COPIES: (202) 366-4900

www.phmsa.dot.gov/hazmat/erg/emergency-response-guidebook-erg

About Paradigm

Paradigm is public awareness. We provide public awareness and damage prevention compliance services to assist with the regulatory requirements of 49 CFR 192 and 195, as well as API RP 1162. Since 2001, the oil and gas industry has worked with Paradigm to fulfill public education and community awareness requirements.

Our history of implementing public awareness programs and compliance services pre-dates API RP 1162. Most of the pipeline industry's large, mid-sized and small operators, as well as many local distribution companies utilize Paradigm's compliance services.

In serving our clients, Paradigm performs full-scope compliance programs from audience identification through effectiveness measurement. In addition, we offer consulting services for plan evaluation and continuous improvement. At the completion of each compliance program, we provide structured documentation which precisely records all elements of the program's implementation to assist with audits.

Paradigm leads the way in industry service. Pipeline operators and local distribution companies trust in Paradigm to implement their public awareness and damage prevention programs. Each year we:

- Distribute 25 million pipeline safety communications
- · Compile and analyze roughly 250,000 stakeholder response surveys
- · Facilitate over 1,200 liaison programs
- Implement approximately 1,000 public awareness compliance programs
- Provide audit support and assistance with over 50 public awareness audits

Contact Paradigm for more information regarding custom public awareness solutions.

Contact us:

Paradigm Liaison Services, LLC PO Box 9123 Wichita, KS 67277 (877) 477-1162 Fax: (888) 417-0818 www.pdigm.com









About Virginia 811

Virginia Utility Protection Service, commonly called Virginia 811, is a not-for-profit organization and the designated one-call notification center for Virginia created by Virginia's utilities to protect their underground facilities. Virginia 811 is dedicated to preventing damage to underground utilities and promoting safety in excavation. They provide a vital service by facilitating communication between excavators and locators, operating a 24/7 contact center, receiving locate requests, and dispatching notifications to utility owners across the Commonwealth. Virginia 811 also provides statewide education, resources, and support to promote safe digging practices and compliance with the Underground Utility Damage Prevention Act

Whether you're a homeowner with a shovel or a professional excavator using mechanized equipment, it's vital for safety to contact Virginia 811 and submit a locate request to have underground utility lines marked before beginning any digging or demolition project. Knowing the location of underground utility lines before digging prevents injuries, property damage, and service outages.

You can submit a locate request online at <u>VA811.com</u> or by calling 811 or 1-800-552-7001. The process is **free** and **easy**.

For more information about Virginia 811 and safe digging practices, visit **VA811.com**.

Know what's below. Contact VA811.com before you dig.

	1	TICKETS STATE LAWS & PROVISIONS					NOTIFICATION EXEMPTIONS					NOTIFICATIONS ACCEPTED											
VIRGINIA							р	ned						igging)									
Virginia 811 800-552-7001				 			Membership	ISSI	ķ					\circ								- 1	Ш
Website: www.va811.com				eraç		Clause	μpe	nits	Premarks	nse	se	Ę		(Hand l								- 1	
Hours: Emergency service: 365 days a year, 24 hours a day. Regular service: Monday through Friday, 7:00 AM - 5:00 PM (excluding legal state and national holidays.		n	o)	wide Coverage	Civil Penalties	_	atory Mer	ator Permits Iss	atory Pre	Positive Response	Dig Clause	ige Reporting		Homeowner (H	ad	ulture		ge	n	Emergency	ead	arge Projects	ance Zone
Advance Notice: 2 working days (excluding weekends and legal holidays)	FAX	Online	Mobile	Statewide	Civil F	Emer	Mandatory	Excavator F	Mandatory	Positi	Hand Dig	Damage	POT	Home	Railroad	Agriculture	Depth	Damage	Design	Emer	Overhead	Large	Tolerance
Waiting Period: 48 hours beginning 7:00 AM the next working day after contacting Virginia 811(excluding weekends and legal holidays)	N	Υ	Υ	Υ	Υ	Υ	Υ	N	N	Υ	Υ	N	Υ	Υ	Υ	Υ	N	N	Υ	Υ	N	N	24"
Marks Valid: 15 working days			Г																				
Law Link: https://ya811.com/laws-and-regulation/																							



